

Firelce®

QUICK START GUIDE



FIRELCE EDUCTOR & NOZZLE GUN

Thank you for your purchase! This Quick Start Guide is designed to show you how to Assemble, Operate and Clean your new Firelce Eductor and Nozzle Gun.

Assembly

1. Insert cone into Eductor.
2. Insert gasket into Eductor.
3. Attach shut-off to female side of Eductor
4. Attach hose to shut-off
5. Attach yellow aspirator to Eductor
6. Attach pick-up hose to ball valve

Start-Up

1. Point nozzle away from target
2. Charge the water line to a minimum of 60 (and a maximum of 200) psi
3. Open the bale on the shut-off to start water flow
4. Open the ball valve
5. Check the pick-up hose for suction
6. Insert pick-up hose into a Firelce bucket and educt using a circular motion
7. Once Firelce is flowing, direct nozzle to target until operation is complete

Shut-Down & Clean-Up

1. Direct nozzle away from target
2. Remove the pick-up hose from the Firelce bucket
3. Inspect the pick-up hose to make sure no more powder is flowing into the Eductor
4. When Firelce is no longer flowing through the hose, close the ball valve
5. Close the bale on the shut off to stop water flow
6. Disassemble all components and rinse thoroughly
7. Blow out pick-up hose to ensure there is no remaining powder

System Components

- Shut Off / Two Hoses
- Eductor / Aspirator
- Pick-up Tubes (2) / Clean-out Brush

Eductor Components

- Aluminum Eductor Body
- Gasket / Cone / Ball Valve
- GHT 1" to ¾" Adapter



Firelce Eductor Gun Breakdown



CAUTION

KEEP PICK-UP TUBE AND HOSE DRY

Water will cause a clog and impair or prevent performance of the Eductor



1460 Park Lane South, Suite 1 • Jupiter, FL 33458
Toll Free 1-844-FIREICE • www.Firelce.com

